

AC750 Wireless Dual Band 4G LTE Router

Share Your 4G LTE Network









Highlights


Superfast 4G LTE Speed & Stream-Ready AC Wi-Fi

The Archer MR202 uses 4G LTE technology to achieve speeds of up to 150 Mbps download and 50 Mbps upload. It also shares a simultaneous dual band Wi-Fi network with maximum speeds of 300 Mbps on 2.4 GHz and 433 Mbps on 5 GHz for gaming, streaming and more.[†]

300 Mbps 2.4 GHz 4G LTE 150 Mbps Add LTE 150 Mbps Areas On Vacation Ideal Use Places

Design for Maximum Network Coverage

Advanced LTE antennas make efficient and stable connections to every device. Power Amplifier and Low Noise Amplifier boost sending and receiving capabilities, creating a wide-coverage Wi-Fi network for your home.



Highlights


Plug and Play

Simply insert your 3G/4G nano SIM card into the built-in slot, turn on the MR202 and start surfing.



More Devices, More Stability

Connect up to 64 wireless devices with ease, thanks to a powerful processor that boosts data transfer speeds while ensuring dependable network stability.



Highlights

Support TP-Link OneMesh™

Co-work with TP-Link OneMesh products, to provide a more flexible and cost-effective Mesh network with a single Wi-Fi name for seamless whole-home coverage.

*OneMesh Range Extender or Powerline Adapter sold separately.



Range Extender


Archer MR202



Scan for compatible products

Available WAN Connection


The WAN/LAN port enables MR202 to work as a traditional wireless router which is compatible with cable, fiber, and DSL modems. And when it's set as a wireless router, its 3G/4G connection works as a backup to provide a sustained and reliable internet connection for you.



Features







4G LTE

- · 4G LTE Ideal for cutting-edge 4G LTE network
- · Backward Compatible Compatible with 3G network

Wi-Fi Speed

- Superior Wireless Speed Combined wireless speeds up to 300 Mbps over 2.4 GHz, and 433 Mbps over 5 GHz
- · 802.11 ac Standard– Provides a data transfer rate 3 times faster than 802.11n for each stream

Wi-Fi Range

· Great Coverage – Better coverage with integrated Wi-Fi omnidirectional antennas

Features







Reliability

- Simultaneous Dual Band Separate Wi-Fi bands enable more devices to connect to your network without a drop in performance
- · Easy Bandwidth Management Advanced QoS makes it easier for you to manage the bandwidth of connected devices
- · Superior Stability Powerful processor enables you to connect up to 64 wireless devices with ease

Ease of Use

- · Intuitive Web UI Ensures quick and simple installation without hassle
- Fast Encryption One-touch WPA wireless security encryption with the WPS button
- Wi-Fi On/Off Conveniently turn on or off wireless radios as required
- Hassle-free Management with Tether App Network management is made easy with the TP-Link Tether App, available on any Android and iOS device
- · Online Upgrade Keeps you informed of the latest firmware and allows online upgrade on the web Ul


Security

- Guest Network Keeps your main network secure by creating a separate network for friends and visitors
- Access Control Establishes a whitelist or blacklist to allow or restrict certain devices to access the internet
- Parental Controls Restrict internet access time and contents for your children's devices
- · Encryptions for Secure Network WPA-PSK and WPA2-PSK encryptions provide active protection against security threats

Specifications

Hardware

- · Interface: 3 10/100Mbps LAN Ports, 1 10/100Mbps LAN/WAN Port, 1 nano SIM Card Slot
- · Buttons: WPS/Wi-Fi Button, RESET Button
- · Antennas: 2 Detachable External 4G LTE Antennas
- External Power Supply: 12V/1A
- Dimensions (W x D x H): $6.85 \times 4.9 \times 1.32$ in $(174 \times 124.5 \times 33.5$ mm)



Wireless

Network Type

4G: FDD-LTE B1/B3/B5/B7/B8/B20/B28 (2100/1800/850/2600/900/800/700 MHz)
TDD-LTE B38/B40/B41 (2600/2300/2500 MHz)

3G: DC-HSPA+/HSPA+/HSPA/UMTS B1/B5/B8 (2100/850/900 MHz)

- · Wireless Standards: IEEE 802.11a/n/ac 5 GHz, IEEE 802.11b/g/n 2.4 GHz
- Frequency: 2.4 GHz and 5 GHz
- · Signal Rate: 300 Mbps at 2.4 GHz, 433 Mbps at 5 GHz
- EIRP (CE): < 20 dBm (2.4 GHz), < 23 dBm (5 GHz)
- · Reception Sensitivity:

5 GHz:

11a 54M: -77 dBm

 11ac VHT20 MCS0: -95.5 dBm
 11ac VHT20 MCS8: -73 dBm

 11ac VHT40 MCS0: -93 dBm
 11ac VHT20 MCS9: -68 dBm

 11ac VHT80 MCS0: -90 dBm
 11ac VHT20 MCS9: -65 dBm

2.4 GHz:

11g 54M: -74.5 dBm

· Wireless Function: Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics

· Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

Specifications

Software

· Operating Modes: 3G/4G Router, Wireless Router

· WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)

· DHCP: Server, DHCP Client List, Address Reservation

· Quality of Service: Bandwidth Control

· Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ

· Dynamic DNS: DynDns, NO-IP

· VPN Server: PPTP VPN, OpenVPN

· Firewall Security: DoS, SPI Firewall, IP and MAC Address Binding

· Protocols: IPv4, IPv6

· Management: Access Control, Local Management, Remote Management, reboot schedule

· Guest Network: 2.4 GHz guest network x 1, 5 GHz guest network x 1

For more information, please visit

https://www.tp-link.com/products/details/?model=Archer+MR202 V1

or scan the QR code left

Attention: This device may only be used indoors in all EU member states, EFTA countries and Northern Ireland. Attention: This device may only be used indoors in Great Britain.

Specifications are subject to change without notice.

[†]Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless coverage are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

Actual network speed may be limited by the rate of the product's Ethernet WAN or LAN port, the rate supported by the network cabel, Internet service provider factors and other environmental conditions.

Maximum 4G download and upload speeds depend on ecternal factors such as the local 4G network capea, the rate supported by the rate of the product's Ethernet want of Lan port, the rate supported by the rate of the product's entire rate of the rat

Others

· Certification:

CE, RoHS

· Requirements:

Edge, Firefox, Chrome, Safari, or other JavaScript-enabled browser

*You are recommended to use the latest version

nano SIM Card

· Environment:

Operating Temperature: 0°C~40°C (32°F~104°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents

AC750 Wireless Dual Band 4G LTE Router Archer MR202

RJ45 Ethernet Cable

Power Adapter

Quick Installation Guide

www.tp-link.com